
MECHANICAL REINFORCING BAR SPLICING SYSTEM

fastCOUP Coupler

PROPERTIES

- No special bar-end treatment gives the ability to connect virtually any bar condition
- Only one-man needed to operate portable pin-driver
- Installs easily and fast
- Easy field adjustability provides greater job site versatility
- Available in sizes 12 mm - 20 mm
- Allows simple visual inspection



Fastcoup Couplers consists of an oval shaped steel sleeve and a wedge pin. The sleeve is placed around two steel bars that overlap. The wedge pin is placed on the sleeve and inserted into a handheld hydraulic pin driver. The pin is then driven to complete the connection through the pre-drilled hole in the sleeve and between the bars. In seconds, a pin is driven.

Typical applications include road repair, bridge repair, precast elements, spiral reinforcement connection, stirrups and ties.



*Fastcoup compatible
Pin Driver is supplied by
Regbar upon request.*

Bridgescoupl couplers are designed to meet or exceed major international building codes including:

AASHTO	ACI 349	IBC Type 1 (125% Specified Yield)	NF A 35-020-1
ABNT NBR 8548:1984	ACI 359	Eurocode 2	GOST 34278
ACI 318 Type 1 (125% Specified Yield)	AS3600	ISO 15835	Turkish Seismic Code 2018

HEADQUARTERS

Caferağa Mah. Albay Faik Sözdener Cad.
No:7/23 Kadıköy- İstanbul / TURKEY
Phone : +90 216 405 21 55 / PBX
info@regbar.com

PLANT


Sanayi Mah. İzmit Sanayi Sitesi
13. Cadde 318 Blok Apt. No:318/132
No:9 İzmit-Kocaeli / TURKEY
Mobile: +90 541 932 3751

RUSSIA BRANCH:

Lesnaya Plaza 4, 4th, Lesnoy Pereulok
No:24/8125047 Moscow / RUSSIA
W: +7 (495) 641 37 64

SIMPLE INSTALLATION


1. Position the sleeve onto the rebar; bar ends must be at least flush with sleeve ends.



2. Position the pin-driver on the coupler and drive the pin.

Product Code	Bar Sizes			Length*		Width*		Unit Weight (*)	
	Metric [mm]	US	Canada	[mm]	["]	[mm]	["]	[kg]	[lb]
FSCP12	12	#4	10M	48	1-5/8	27	1-1/16	0.2	0.45
FSCP16	16	#5	15M	57	1-15/16	33	1-5/16	0.34	0.75
FSCP20	20	#6	20M	70	2-3/8	40	1-15/16	0.62	1.37

(*) Dimensions and weights may vary by country.

NOTES

- Dimensions shown in chart are typical.
- Refer to the complete product installation instructions before starting the installation.

Regbar Construction
Reinforcing Bar
Splicing System
<http://tiny.cc/regbar>


HEADQUARTERS

Caferağa Mah. Albay Faik Sözdener Cad.
No:7/23 Kadıköy- İstanbul / TURKEY
Phone : +90 216 405 21 55 / PBX
info@regbar.com

PLANT

Sanayi Mah. İzmit Sanayi Sitesi
13. Cadde 318 Blok Apt. No:318/132
No:9 İzmit-Kocaeli / TURKEY
Mobile: +90 541 932 3751

RUSSIA BRANCH:

Lesnaya Plaza 4, 4th, Lesnoy Pereulok
No:24/8125047 Moscow / RUSSIA
W: +7 (495) 641 37 64